

Technical Data Sheet

CODE 70904

EASY DRY AUTO

Automatic and manual hair and hand dryers




Certifications



TECHNICAL AND PERFORMANCE DATA

Absorbed Current max (A)	8	Shock resistance rating (IK)	09
Absorbed Power max (W)	1800	Voltage (V)	220-240
Frequency (Hz)	50/60	Weight (Kg)	3,1
Insulation Class	II°	Delivery max (l/s)	37,5
IP	X4	Delivery max (m³/h)	135
Motor Power (W)	70/85	Power in stand-by mode (W)	0.49
		Sound pressure level Lp [dB (A)] 1m	61

DIMENSIONS



Size A (mm)	346
Size B (mm)	265
Size C (mm)	133
Size D (mm)	155

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com

Technical Data Sheet

CODE 70904

EASY DRY AUTO

Automatic and manual hair and hand
dryers



DESCRIPTION

- Front cover made of shockproof, UV-resistant plastic (ABS); closure system with allen screw.
- Rear flange moulded in self-extinguishing polypropylene (PP).
- Lower grille and mesh filter moulded in plastic resin (PC).
- Induction motor with thermal overload cutout, coupled to centrifugal impeller.
- Heating element protected by 2 devices: thermal fuse and resettable thermal overload limiter.
- Dryer operated automatically by an infrared device with activation distance of up to 35 cm, selected by means of an internal trimmer adjustable at the moment of installation. Appliance shuts down automatically in the event of the sensor being obstructed intentionally or accidentally, after 10' continuous operation.
- IMQ safety certification.

PER INFORMAZIONI:

Servizio al Cliente: tel +39 02 90699395 premendo 1 dopo messaggio registrato (consulenza su prodotti e impianti)

Pre & Post Vendita: fax +39 02 90699302

Email prevendita: prevendita@vortice-italy.com