CE



VORTDRY 1000 RANGE

Hair dryers with flexible hose

Ideal for use in hotels and the home.

- 2 models: VORTDRY 1000, VORTDRY 1000 PLUS and VORTDRY 1000 JET (with and without razor socket).
- Automatic hose hair dryer for wall mounting.
- Flexible spiral PVC hose.
- Front cover in self-extinguishing V0 ABS resin.
- Hose extends from 500 to 1600 mm.
- PLUS version equipped with razor sockets for 230 V / 50 Hz and 110 V / 60 Hz power, with overload protection.
- The heating element is protected by two safety devices (automatic reset thermal cutout and thermal fuse).
- Washable dust filter: protects internal parts and guarantees reliable, low maintenance operation.
- Integrated automatic stop: the unit switches off when the blower is replaced, or after around 20 minutes of continuous operation.
- The blower's ergonomic design ensures a sure grip even with wet hands. Its internal core prevents overheating, which can be uncomfortable when used for a long time.
- Protection rating: IPX4.
- IK: 6 for VORTDRY 1000 AND VORTDRY 1000 PLUS;
 9 for VORTDRY JET. (Tested to withstand even the hardest impact IK test).
- Insulation class: II.□







Wiring diagrams shown from page 458














TECHNICAL DATA


Models	Code	V ~ 50/60 Hz	w	W motor	W Stand-by	Α	Max Airflow		Lp dB(A)
							m³/h	I/s	1 m
VORTDRY 1000	70920	230	1000	120	0.5050	4.7	114	31.6	68
VORTDRY 1000 PLUS	70921								
VORTDRY 1000 JET	70919		800	90	0.5110	3.5	190*	52.7*	62

^{*} The airflow refers to air flowing along non-corrugated surface with no joints.



DIMENSIONS





Models	Α	В	С	D	Kg
VORTDRY 1000	190	300	130	550	1.5
VORTDRY 1000 PLUS	190				

Dimensions (mm)

Models	Α	В	С	D	Kg	
VORTDRY 1000	320	380	160	560	3.2	

Dimensions (mm)



